

# pre-dosed amalgam capsules permite, lojic+ & gs-80

## INSTRUCTIONS FOR USE

N

G L

> I S

Indications for use: Filling material as a treatment for dental caries.

Contra-indications for use: Do not use in persons with a known mercury allergy.

Permite: The non-gamma 2 admix alloy unsurpassed by any other with its high strength, high polishability and superior handling qualities. The alloy to mercury ratio varies between 1/0.86 and 1/0.96 depending on the size and setting time, i.e. 46.2% to 49.5% by weight mercury. The compressive strength of Permite at 24 hours is 500 MPa, and the dimensional change during hardening is +0.04%.

Lojic+: The platinum modified, high silver, non-gamma 2 spherical amalgam. Lojic+ has exceptional early strength, smooth handling and excellent polishability. The alloy to mercury ratio varies between 1/0.73 and 1/0.78 depending on the size and setting time, i.e. 42.2% to 43.8% by weight mercury. The compressive strength of Lojic+ at 24 hours is 520 MPa, and the dimensional change during hardening is -0.04%.

GS-80: The technically advanced, non-gamma 2 admix amalgam at an affordable price.
GS-80's high strength ensures longevity and patient satisfaction. The alloy to mercury ratio varies between 1/0.85 and 1/0.94 depending on the size and setting time, i.e. 45.9% to 48.5% by weight mercury. The compressive strength of GS-80 at 24 hours is 510 MPa, and the dimensional change during hardening is +0.02%. coloured plunger denotes the spill size, whilst the coloured base indicates the setting

		Mercury (mg)							
Spill	Plunger	Alloy (mg)	Fast (blue)	Regular (grey)	Slow (cream)	ECT (green)			
• Permite									
1	pink	400	344	364	380	372			
2	purple	600	522	552	576	564			
3	yellow	800	696	736	768	752			
5	dark green	1200	-	1128	-	-			
Working time:									
Condensing time (minutes)			2.5	3.5	4.5	5			
Carving time (minutes)			5.5	5.5	5.5	7			
• Lojic+									
1	orange	400	292	304	308				
2	cream	600	438	456	462				
3	brown	800	584	608	616				
5	cerise	1200	-	936	-				
Working time:									
Condensing time (minutes)			2.5	3	4				
Carving time (minutes)			4.5	6	6				
• GS-80									
1	grey	400	346	360	376				
2	light green	600	510	540	564				
3	burgundy	800	680	720	752				
5	gold	1200	-	1116	-				
Working time:									
Condensing tir			3.5	4.5	5.5				
Carving time (r	minutes)		5.5	5.5	5.5				

Laving time (minutes)

5.5

5.5

INSTRUCTIONS:

1. Select the appropriate size capsule according to colour coding.

2. With the capsule inverted, SLOWLY press the plunger end of the capsule against a flat surface (see figure 1) until the flange of the plunger is flush with the capsule body (see figure 2). THIS IS MOST IMPORTAMT. Initially, resistance will be felt, then suddenly released as the plunger pierces a diaphragm allowing the mercury to enter the mixing chamber.

3. Slightly spread the amalgamator (logs and carefully insert the capsule. Ensure that the capsule is securely anchored between the clips. (see figure 3).

4. Select the appropriate mixing time from the suggested mixing times (see table 1). A range of mixing times is given to accommodate mixing variations that can occur due to machine type, age and line voltage. Correctly triturated amalgam will form into a bright homogeneous plastic mass. A hot, shiny, sticky mass indicates over trituration whilst a dull, dry or powdery mass is under triturated.

5. After trituration has been completed, carefully remove the capsule from the clip.

6. Tap the base end of the capsule sharply on the bench to ensure that the mixed amalgam is located in the base of the capsule (see figure 4).

7. Separate the base from the body and remove the prepared amalgam from the capsule. If the small separating diaphragm has come away from the capsule wall during activation and mixing, it will separate cleanly from the amalgam.

8. CONDENSATION:

Moisture contamination: If moisture has introduced into the amalgam before it has set, properties such as strength and corrosion resistance may be affected adversely. If the alloly contains zinc, such contamination may result in an excessive expansion (delayed expansion). Whenever it is possible, use a dry field. Insertion of the amalgam should commence immediately after trituration. It is not necessary to express mercury prior to insertion. Traditional condensation techniques are recommended. Pack angles and undercuts with a small-f

WARNING - CONTAINS MERCURY
DANGER - POISON
May be harmful if vapours are inhaled. Avoid breathing.
Keep container closed. Use with adequate ventilation.

Do not open capsules prior to trituration. Do not remove the coloured plunger from the capsule. The wearing of gloves, glasses and protective clothing is recommended for all dental procedures. Dispose of used capsules in accordance with national regulation - Ingestion: Mercury may cause neurotoxic effects and renal damage.

Inhalation: Mercury may cause respiratory disorders including inflammation and fluid retention.

- retention. Eyes & Skin: Mercury may cause irritations and allergic reactions. Acute Exposure: Mercury may cause irritations and allergic reactions including dermatitis, digestive and respiratory disorders.
- California Prop 65 Warning: This product contains mercury, a chemical known to the State of California to cause birth defects or other reproductive harm.

Health Canada Warning: (1) Non-mercury filling materials should be considered for restoring the primary teeth of children where the mechanical properties of the material are suitable. (2) Wherever possible, amalgam fillings should not be placed in or remove from the teeth of pregnant women. (3) Amalgam should not be placed in patients with impaired kidney function. (4) In placing and removing amalgam fillings, dentists should use techniques and equipment to minimize the exposure of the patient and the dentist mercury vapour and to prevent amalgam waste from being flushed into municipal sewa systems. (5) Dentists should advise individuals who may have allergic hypersensitivity to mercury to avoid the use of amalgam. In patients who have developed hypersensitivity amalgam, existing amalgam restorations should be replaced with another material when this is recommended by a physician.

amalgam, existing amalgam restorations should be replaced with another material where this is recommended by a physician.

The U.S. FDA states the following on dental amalgams: Dental amalgam has been demonstrated to be an effective restorative material that has benefits in terms of strength, marginal integrity, suitability for large occlusal surfaces, and durability. Dental amalgam also releases low levels of mercury vapor, a chemical that at high exposure levels is well-documented to cause neurological and renal adverse health effects. Mercury vapor concentrations are highest immediately after placement and removal of dental amalgam but decline thereafter. Clinical studies have not established a causal link between dental amalgam and adverse health effects in adults and children age six, and older. In addition, two clinical trials in children age six and older did not find neurological or renal injury associated with amalgam use. The developing neurological systems in fetuses and young children may be more sensitive to the neurotoxic effects of mercury vapor. Very limited to no clinical information is available regarding long-term health outcomes in pregnant women and their developing fetuses, and children under the age of six, including infants who are breastfed. The Agency for Toxic Substances and Disease Registry's (ATSDR) and the Environmental Protection Agency (EPA) have established levels of exposure for mercury vapor that are intended to be highly protective against adverse health effects, including for sensitive subpopulations such as pregnant women and their developing fetuses, breastfed infants, and children under age six. Exceeding these levels does not necessarily mean that any adverse effects will occur. FDA has found that scientific studies using the most reliable methods have shown that dental amalgam exposes adults to amounts of elemental mercury vapor below or approximately equivalent to the protective levels of exposure identified by ATSDR and EPA. Based on these findings and the clinical da

**CAUTION:** Federal law restricts this device to sale by or on the order of a dentist. **Keep out of the reach of children.** Single use only. Do not place the device in direct contact with other types of metals.

Spillages: Mercury presents a health hazard if incorrectly handled. Spillages of mercu should be removed immediately, including from places which are difficult to access. U a plastic syringe to draw it up. Smaller quantities can be covered by sulfur powder are removed. Avoid inhalation of the vapour.

The information provided herein is given in good faith, but no warranty expressed or implied is made. MSDS available at www.sdi.com.au or contact your regional representative.

**STORAGE:** It is recommended that this product be stored at temperatures below 25°C / 77°F in a well ventilated place.

 Composition of alloys:

 Permite:
 Ag 56%, Sn 27.9% Cu 15.4%, In 0.5%, Zn 0.2%

 THIS ALLOY CONTAINS ZINC; THE AMALGAM MADE THEREFROM MAY SHOW EXCESSIVE EXPANSION IF MOISTURE IS INTRODUCED DURING MIXING OR CONDENSING.

 Lojic4:
 Ag 60.1%, Sn 28.05%, Cu 11.8%, Pt 0.05%

 GS-80:
 Ag 40%, Sn 31.3%, Cu 28.7%

Permite, Lojic+ and GS-80 capsules conform to ISO 24234 and ANSI/ADA Specification No.1. Date of last Review: July 2010

### AMERICAN DENTAL ASSOCIATION MECHANICAL AMALGAMATION REQUIREMENT SDI ULTRAMAT 2

AMALGAMATOR Cycles per second Time of Mixing (Seconds) Plastic Capsules

8 (2 spill regular setting tim

Made in Australia by SDI Limited Bayswater, Victoria 3153 Australia 1 800 337 003 Austria 00800 022 55 734 Brazil 0800 770 1735 France 00800 022 55 734 Germanu 0800 102 7579 United Kingdom 00800 022 55 734 USA & Canada 1 800 228 5166 www.sdi.com.au France 00800 022 55 734 Germany 0800 100 5759 Ireland 01 886 9577 Italy 800 780625 New Zealand 0800 734 034 Spain 00800 022 55 734

EC REP

SDI Dental Limited Block 8, St Johns Court Swords Road, Santry Dublin 9, Ireland Tel +353 1 886 9577

Figure 1, Abbildung 1, Figura 1, | 图 ] Rycina 1



Figure 3, Abbildung 3, Figura Rycina 3 3. 图 3





Figure 4, Abbildung 4, Figura 4, 👰 4 Rycina 4



Table 1, Tabelle 1, Tabela 1, Tabla 1, Tabela 1, Tableau 1, Tabela 1 表1
Recommended amalgamator settings / Valores recomendados / Empfohlene Mischzeite
verschiedene Mischgeräte/ Tempi di miscelazione suggeriti / Reglages recommandés de
'/ Yamalgamateur/ Tiempo recomendado de mezcla / Zalecane ustawienia mieszalnika.
推荐的银汞调拌机设置

Trituration time			lojic+		gs-80	
speed	1,2, 3	5	1,2,3	5	1,2,3	5
setting	spill	spill	spill	spill	spill	spill
Fixed	8±1	6±1	6±1	6±1	8±1	6±1
	8±1	7±1	8±1	7±1	8±1	7±1
M2	8±2	7±2	8±2	7±2	8±2	7±2
M	8±2	7±2	8±2	7±2	8±2	7±2
Fixed	7±1	6±1	6±1	6±1	8±1	7±1
Wig-L-Bug (Crescent):						
Medium	10±2	9±2	9±2	8±2	10±2	9±2
	20±5	18±5	20±5	18±5	20±5	18±5
Low	10±2	9±2	9±2	8±2	10±2	9±2
Low	20±2	18±2	20±2	18±2	20±2	18±2
3500 CPM	10±2	9±2	9±2	8±2	10±2	9±2
Executive (Pelton Crane)		9±2	9±2	8±2	10±2	9±2
Fixed	12±2	10±2	11±2	10±2	12±2	10±2
3800 CPM	10±2	9±2	8±2	7±2	10±2	9±2
M	10±2	9±2	8±2	7±2	10±2	9±2
3600 CPM	10±1	9±1	9±2	8±2	10±1	9±1
	setting Fixed  M2 M Fixed  Medium  Low J500 CPM  Fixed  Medium  Low J500 CPM  MM	speed setting Fixed         1,2, 3 spill           M2         8±1           M2         8±2           Fixed         7±1           Medium         10±2           Low         10±2           Low         20±5           Low         10±2           Fixed         10±2           Fixed         12±2           M         10±2           M         10±2	setting         spill         spill           Fixed         8±1         6±1           8±1         7±2           M2         8±2         7±2           M         8±2         7±2           Fixed         7±1         6±1           Medium         10±2         9±2           Low         20±5         18±5           Low         20±2         18±2           Low         20±2         18±2           3500 CPM         10±2         9±2           Fixed         12±2         10±2           M         10±2         9±2           M         10±2         9±2	speed setting Fixed         1,2,3 spill	speed setting         1,2,3 spill         5 spill         1,2,3 spill         5 spill         spill spill           Fixed         8±1         6±1         6±1         6±1         6±1         6±1         6±1         6±1         6±1         6±1         7±1         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         0±2         8±2         8±2         20±5         18±5         20±5         18±5         20±5         18±5         20±2         18±2         20±2         18±2         20±2         18±2         20±2         18±2         20±2         18±2         3±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2         7±2         8±2	speed setting Fixed         1,2,3 spill

The ESPE Rotomix is not recommended for mixing SDI amalgam capsules. Capmix, Vari-Mix II, Vari-Mix III, Silamat, Wig-L-Bug, Spirit, Executive, Torit, Duomat, Zenith, AutoMix and Rotomix are not the registered trademarks of SDI Limited.

WICHTIG: Der ESPE Rotomix wird nicht zum Anmischen von SDI Kapseln empfohlen.Capmix, Vari-Mix II, Vari-Mix III, Silamat, Wig-L-Bug, Spirit, Executive, Torit, Duomat, Zenith, AutoMix und Rotomix sind keine geschützten Produkte der Firma SDI Ltd.

OBSERVAÇÃO: O Rotomix ESPE não é recomendado para misturar as cápsulas de amálgama da SDI. Capmix, Vari-Mix II, Vari-Mix III, Silamat, Wig-L-Bug, Spirit, Executive, Torit, Duomat, Zenith, AutoMix e Rotomix não são marcas registradas da SDI Limited.

NOTA:

El ESPE Rotomix no está recomendado para mezclar las cápsulas de amalgama SDI. Capmix, Vari - Mix II, Vari - Mix II, Silamat, Wig - L - Bug, Spirit, Executive, Torit, Duomat, Zenith, Automix y Rotomix no son marcas registradas de SDI Limited.

NOTE:

Le ESPE Rotomix n'est pas recommandé pour mélanger les capsules d'amalgame SDI. Capmix, Vari-Mix II, Vari-Mix III, Silamat, Wig-L-Bug, Spirit, Executive, Torit, Duomat, Zenith, AutoMix et Rotomix ne sont pas des marques déposées de SDI Limited.

pas des filarques deposes de 251 millione. Il miscelatore Rotomix ESPE non è adatto per la miscelazione delle capsule di amalgama SDI. Capmix, Vari-Mix II, Vari-Mix III, Silamat, Wig-L-Bug, Spirit, Executive, Torit, Duomat, Zenith, AutoMix and Rotomix non sono marchi registrati da SDI Limited. NOTA:

不建议用ESPE Rotomix来混合SDI银汞胶囊。Capmix、Vari-Mix II/III、 at、Wig-L-Bug、Spirit,Executive、Torit、Duomat, Zenith、AutoMix和 Silamat、Wig-L-Bug、Spirit、Executive、 Rotomix不是SDI Limited公司注册的品牌。