

Report No.: RSZBHS1241203837-2 Date of Issue: Jan.08 2022

Approved by 批准:

1. PRODUCT AND COMPANY IDENTIFICATION 产品和公司基本信息

111112	AND IDENTIFICATION OF THE PROPERTY OF THE PROP
Product Detail 产品详情	
Product Name:	Rechargeable Lithium-ion Polymer Battery
产品名称:	可充电锂离子聚合物电池
Product Use:	Used in portable applications
产品使用:	用于便携式应用
Model: 型号:	ZN 103450
Supplier Name:	GUANGDONG ZHAONENG TECHNOLOGY CO.,LTD.
申请商名称:	广东兆能科技有限公司
Supplier Address: 申请商地址:	No. 11 , Dou Kou Development Zone Avenue , Xia Jiao Village, Dan Zao Town, Nanhai district, Foshan city Guangdong, China 广东省佛山市南海区丹灶镇下滘村窦口开发区大道 11 号
Supplier Phone Number: 申请商号码:	+86-0757-81289782
Emergency telephone number: 紧急联系号码:	+86-0757-81289782

1 / 13



2. COMPOSITION / INFORMATION ON INGREDIENTS 成分及组成信息

Ingredient Name 成分名称	CAS No. CAS号(化学文摘索引登记 号)	Percent of Content (%)含量百分比
Lithium Cobalt Oxide		
(CoLiO2)/钴酸锂	12190-79-3	12 – 39
Copper /铜	7440-50-8	12 – 26
Graphite /石墨	7782-42-5	14 – 27
Ethylene carbonate	96-49-1	
碳酸亚乙酯		10– 23
Phosphate(1-), hexafluoro-,		
lithium /磷酸锂	21324-40-3	8 – 15
Aluminum foil /铝	7429-90-5	6 – 13

Note 注:

Labeling according to directives.

标签根据 EC 指令

No symbol and Hazard phrase are required.

不需要象形符号和危险短语。

Percent of Content is the range value

含量百分比是范围值

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CAS 号是化学文摘服务注册号

EC#: European Inventory of Existing Commercial Chemical Substances.

欧洲现有商业化学品目录

2 / 13

Phone: +86 755 8650 3482 Check: cs@hc-stc.net Website: http://wwwh.hc-stc.net



N/A=Not apply.

N/A=不适用。

3. HAZARDS IDENTIFICATION 危险性概述





Hazard description: Harmful! Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion.

危害说明:有害! 请勿短路,充电,穿刺,焚烧,挤压,浸泡,强制放电或暴露在高于 产品声明的工作温度范围的温度下。 有火灾或爆炸的危险。

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

在正常使用条件下,它们所含的电极材料和液体电解质不会暴露在外面,只要保持电池 完整性并且密封保持完整。 仅在滥用(机械,热,电)的情况下暴露风险,这会导致安全阀的激活和/或电池容器的破裂。 根据具体情况,可能会出现电解液泄漏,电极材料与湿气/水反应或电池通风/爆炸/火灾。

4. FIRST-AID MEASURES 急救措施

Eyes: Irrigate thoroughly with water for at least 15 minutes. Obtain medical

眼睛: attention.



	用水彻底冲洗至少15分钟。迅速就医。
Skin:	Wash off skin thoroughly with water. Remove contaminated clothing
皮肤:	and wash before reuse. In severe cases obtain medical attention.
	用水彻底冲洗皮肤。 脱去污染的衣服,并在重新使用前清洗。 在严
	重的情况下迅速就医。
Inhalation:	Remove from exposure, rest and keep warm. In severe cases obtain
mnalation. 吸入:	medical attention.
吸入.	暴露,休息和保暖。在严重的情况下迅速就医。
Ingestion	Wash out mouth thoroughly with water and give plenty of water to
Ingestion: 摄入:	drink. Obtain medical attention.
放人.	用水彻底冲洗口腔,并喝足够的水。迅速就医。
	All cases of eye contamination, persistent skin irritation and
Furth or trootmont.	casualties who have swallowed this substance or been affected by
Further treatment:	breathing its vapours should be seen by a Doctor.
进一步治疗: 	医生应该看到所有眼睛污染,持续性皮肤刺激和吞咽这种物质或受到
	蒸气呼吸影响的人员。

5. FIRE-FIGHTING MEASURES 消防措施		
Hazardous	When burned, hazardous products of combustion including	
Combustion Products:	fume of carbon monoxide and carbon dioxide can occur.	
有害燃烧产物:	燃烧时,会产生包括一氧化碳和二氧化碳的燃烧的有害燃烧物。	
Extinguishing Media:	Water, carbon dioxide, dry chemical or foam.	
灭火介质:	水,二氧化碳,干化学品或泡沫。	
	Wear NIOSH/MSHA approved positive pressure self-contained	
Basic Fire Fighting	breathing apparatus and protective clothing to prevent contact	
Procedures:	with skin and eyes.	
基本消防程序:	佩戴NIOSH / MSHA认可的正压自给式呼吸器和防护服,以防止	
	接触皮肤和眼睛。	

6. ACCIDENTAL RELEASE MEASURES 泄露应急处理

4 / 13

Phone: +86 755 8650 3482 cs@hc-stc.net Website: http://wwwh.hc-stc.net



If the battery breakage and electrolyte leakage, evacuate

personnel until the smoke cleared.

Accidental: 如果电池破损和电解液泄漏,疏散人员直到烟雾消失。

非主要的: Wipe with a cloth and placed in steel drums into the bag inside.

If the battery is hot, away from the scene firstly, cool the battery,

so that the steam dissipated. Adequate ventilation.

用布擦拭,然后将钢桶放入袋内。如果电池很热,请先离开现场,

冷却电池,使蒸汽消散。 通风良好。

Avoid skin or eye contact steam.

避免皮肤或眼睛接触蒸汽。

The battery Should discharge completely, the waste batteries

will be turned over in the relevant sector, and all waste must

refer to the United Nations, national, local regulations for

disposal. Reference to national or federal Environmental

Protection Agency EPA.

电池应完全放电,废电池将在相关部门翻转,所有废物必须参考

联合国,国家和地方的处置规定。 参考国家或联邦环境保护局

EPA.

7. HANDLING AND STORAGE 操作处置与储存

Prohibit mechanical or electrical damage battery.

禁止机械或电气损坏电池。

Waste treatment:

废物处理:

Stored in a dry, cool and ventilated environment, to avoid temperature changes or high temperature.

储存在干燥,阴凉,通风的环境中,避免温度变化或高温。

Keep away from heat, avoid prolonged sun exposure.

远离热源,避免长时间暴露在阳光下。

Against short circuit, overcharge, forced discharge, or in a fire.

防止短路,过充电,强制放电或发生火灾。

Battery disassembly, crush, fire or high temperatures can cause fire or explosion, prohibit short-circuit or error operation.

|电池拆卸,挤压,着火或高温可能引起火灾或爆炸,禁止短路或误操作。

5 / 13



8.EXPOSURE CONTROLS / PERSONAL PROTECTIO 接触控制/个体防护		
Respiratory protection:	If the battery leaks, the need for full ventilation.	
呼吸系统防护:	如果电池漏液,需要充分通风。	
Hand Protection:	Under normal use, do not.	
手部防护:	在正常情况下不需要。	
Personal Protection:	Under normal use, do not.	
个人防护:	在正常情况下不需要。	
Other protection:	Under normal use, do not.	
其他保护:	在正常情况下不需要。	

If the battery leaks, must wear the following protection products.

如果电池漏液,必须佩戴以下保护产品。

	Respiratory Protection 呼吸系统防护	In all fire situations, use self-contained breathing apparatus. 在所有火灾情况下,请使用自给式呼吸器。
my y	Hand Protection 手部防护	In the event of leakage wear gloves. 在发生泄漏时戴上手套。
	Eye Protection 眼睛保护	Safety glasses are recommended during handling. 处理过程中建议使用安全眼镜。
	Other 其他	In the event of leakage, wear chemical apron. 如果发生泄漏,请穿化学防护。

9. PHYSICAL AND CHEMICAL PROPERTIES 理化特性	
Nominal Voltage:	3.7V
标称电压	3.7 V

6 / 13

 $Room\ 202\ ,\ 2/F\ ,\ Building\ F,\ Hao\ Wei\ Industrial\ Park,\ Qing\ Song\ West\ Road,\ Ping\ Shan\ District,\ Shenzhen,\ Guangdong,\ China/518000$



	1
Capacity:	1800mAh
容量	
Watt-hour:	6.66Wh
瓦时	0.000011
Appearance characters:	Silver almost cuboid
外观:	银色近长方体
Size:	
尺寸:	11.0mmx34.0mmx52.0mm
Form:	Solid
,。 物理形态:	m+
初年/22000 .	固态
PH:	Not Applicable
PH值:	不适用
	1 ,22,713
Odour :	Not Applicable
气味:	不适用
Boiling point and Boiling	Not Applicable
range:	不适用
沸点及沸点范围:	个坦用
Flash point :	Not Applicable
闪点:	不适用
. 3///	个坦用
Upper/lower flammability or	Not Applicable
explosive limits:	不适用
易燃或爆炸极限的上限/下限:	1、垣 <i>四</i>
Vapor Pressure:	Not Applicable
蒸汽压:	不适用
Vapor Density:	Not Applicable
蒸汽密度:	
	不适用
Relative density:	Not Applicable
相对密度:	不适用
Auto-ignition temperature:	Not Applicable
自燃温度:	不适用
	. ~~.

7 / 13

Phone: +86 755 8650 3482 cs@hc-stc.net Website: http://wwwh.hc-stc.net $Room\ 202\ ,\ 2/F\ ,\ Building\ F,\ Hao\ Wei\ Industrial\ Park,\ Qing\ Song\ West\ Road,\ Ping\ Shan\ District,\ Shenzhen,\ Guangdong,\ China/518000$



Decomposition temperature:	Not Applicable
分解温度:	不适用
Evaporation rate :	Not Applicable
蒸发速度:	不适用
Flammability (soil , gas):	Not Applicable
可燃性(土壤,空气):	不适用
Viscosity:	Not Applicable
黏度:	不适用

产品在第七部分所诉的条件下稳定。		
Hazardous reactions may occur under some specific conditions.		
在某些特定条件下可能会发	在某些特定条件下可能会发生危险反应。	
	When a battery cell is exposed to an external short-circuit,	
	crushes, modification, high temperature above 100 degree	
	C, it will be the cause of heat generation and ignition. Avoid	
应避免的条件:	to be exposed to direct sunlight and high humidity.	
	当电池暴露在外部短路,压碎,改性,高于 100℃的高温时,	
	它将成为发热和点火的原因。 避免暴露在阳光直射和高湿度	
Conditions to avoid: 应避免的条件:	When a battery cell is exposed to an external short-circuit, crushes, modification, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Avoi to be exposed to direct sunlight and high humidity. 当电池暴露在外部短路,压碎,改性,高于 100°C的高温时	

Conductive materials, water, seawater, strong oxidizers and

10. STABILITY AND REACTIVITY 稳定性和反应活性

的环境中。

strong acids.

Materials to avoid:

要避免的材料:

decomposition

Hazardous

Product is stable under conditions described in Section 7.

Phone: +86 755 8650 3482 Check: cs@hc-stc.net Website: http://wwwh.hc-stc.net Room 202 , 2/F , Building F, HaoWei Industrial Park, QingSong West Road, PingShan District, Shenzhen, Guangdong, China/518000

火灾时会释放出刺激性或有害气体。

8 / 13

导电材料,水,海水,强氧化剂和强酸。 Acrid or harmful gas is emitted during fire.



products:	
危险分解物:	

11. TOXICOLOGICAL	_ INFORMATION 毒理学 资料	
Primary irritant effect: 主要刺激作用:	None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibrotic lung injury and membrane irritation. 无,除非电池破裂。 如果暴露在内部物质中,腐蚀性烟雾会对皮肤,眼睛和粘膜造成很大的刺激。 过度暴露可引起非纤维化肺损伤和膜刺激的症状。	
Inhalation: 吸入:	Lung irritant. 呼吸道有刺激性。	
Skin contact: 皮肤接触:	Skin irritant. 皮肤有刺激性。	
Eye contact: 眼睛接触:	Eye irritant. 眼睛有刺激性。	
Ingestion: 摄入:	Tissue damage to throat and gastro-respiratory tract if swallowed. 吞咽会对喉咙和胃肠道造成组织损伤。	
Medical conditions generally aggravated by exposure: 暴露会加剧医疗条件:	In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur. 如果接触到内部物质,可能会发生湿疹,皮肤过敏,肺部损伤,哮喘和其他呼吸系统疾病。	
12. ECOLOGICAL INFORMATION 生态学资料		
Environmental Impact: 对环境造成的影响:	Proper use and disposal of the battery will not harm the environment. Dispose of the battery, away from water, rain and snow. 正确使用和处理电池不会损害环境。处理电池,远离水,雨和雪。	

9 / 13

Phone: +86 755 8650 3482 cs@hc-stc.net Website: http://wwwh.hc-stc.net



13. DISPOSAL CONSIDERATIONS 废弃处置

Do not incinerate, or subject cells to temperatures in excess of 100°C. Such abuse can result in loss of seal, leakage, and/or cell explosion.

不要焚烧或使细胞温度超过100℃。 这种滥用可导致密封,泄漏和/或细胞爆炸的丧失。

Waste disposal must be in accordance with the applicable regulations. Disposal of the lithium ion battery cells should be performed by permitted, professional disposal page: firms knowledgeable in state or local requirements of hazardous waste treatment and hazardous waste transportation. Incineration should never be performed by battery but users, eventually by trained professional in authorized facility with proper gas and fume treatment.

废物处理必须符合适用法规。 锂离子电池的处理应通过允许的专业处理页面进行:公司 了解危险废物处理和危险废物运输的州或地方要求。 焚烧不应该由电池进行,而是由用 户进行,最终由经过授权的设施中经过培训的专业人员进行适当的气体和烟气处理。

Deserted batteries could not be treated as ordinary trash. could not be thrown into fire or placed

in high temperature. could not be dissected, pierced, crushed or treated similarly. Best way is recycling.

废弃的电池不能被视为普通垃圾。 不能被扔进火里或被放置在高温下。 不能被解剖,刺 穿,压碎或类似处理。 最好的方法是回收。

14. TRANSPORT INFORMATION 运输信息

ICAO/IATA:	Can be shipped by air in accordance with international Civil
国际民间航空组织/国	Aviation Organization (ICAO), TI or International Air Transport
	Association (IATA) DGR 63 rd Packing Instructions Section IB of
际航空运输协会:	965 or Section II of 966 /967 appropriately
	可以按照国际民用航空组织(ICAO),国际航空运输协会(IATA)
	DGR第63号包装说明PI965 Section IB或PI966、PI967 Section
	Ⅲ的规定空运。
IMDG CODE :	The batteries are not restricted to IMDG Code 2020 Edition
│ │国际海运危险货物规	Amdt 40-20.according to special provision 188
	根据特殊规定 188,该电池不受 IMDG Code 2020 版(Amdt
则:	
	40-20)限制。

10 / 13

Phone: +86 755 8650 3482 Check: cs@hc-stc.net Website: http://wwwh.hc-stc.net



ADR/AND: 欧洲国际陆运危险货物协定/关于内陆水道 国际运输危险货物的	European Agreement concerning the International Carriage of Dangerous Goods by Road under Special Provision 188 根据特别条款 188 的欧洲国际公路运输危险货物协定
欧洲协定: UN number: UN 编号:	UN3480 or UN 3481 UN3480 或 UN 3481
Label for conveyance 运输标签:	Lithium Battery Label 锂电池标签
Transport hazard class(es) 运输风险类别	9
UN Proper shipping name UN 航运名称	UN3480 Lithium ion Batteries (Including lithium ion polymer batteries) UN3481 PI966 Lithium ion Batteries packed with equipment (including lithium ion polymer batteries) UN3481 PI967 Lithium ion Batteries Contained In Equipment (including lithium ion polymer batteries) UN3480 锂离子电池(包括锂离子聚合物电池) UN3481 PI966 锂离子电池和设备一起(包括锂离子聚合物电池)
	池)



15. REGULATORY INFORMATION 法规信息

《Dangerous Goods Regulation》

《危险物品规则》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《对危险货物运输的有关规定的建议》

《International Maritime Dangerous Goods》

《国际海运危险货物规则》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《危险品安全运输技术指令》

《Classification and code of dangerous goods》

《危险货物分类和品名编号》

OSHA Hazard Communication Standard Status

《职业安全卫生法》

Toxic Substances Control Act (TSCA) Status

《有毒物质控制法》

SARA Title III

《超级基金修正案和再授权法案 Ⅲ(302/311/312/313)》

RCRA

《资源保护及恢复法案》

In accordance with all Federal, State and Local laws

根据所有联邦、州和地方法律。

16. OTHER INFORMATION 其他信息

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

以上信息基于我们所知的数据,并且据信其数据是正确的。 由于此信息可能在我们无法

控制的条件下应用,并且可能不熟悉,并且由于在此数据之后提供的数据可能建议修改



信息,因此我们对其使用结果不承担任何责任。 提供此信息的条件是,收到该信息的人 应自行确定材料是否适合其特定用途。